



medical **ECONET**  
GERMANY

incl.  
Glasgow  
Algorithm



## CARDIO M-PAD 7

Lightweight tablet ECG with 7" touch display

- 7" HR color touch screen, easy to operate. Portable design, compact size
- Built-in rechargeable lithium battery
- Can be powered by an external DC power supply
- Input patient information via virtual alphanumeric keyboard and barcode scanning
- Output files in formats such as: PDF, BMP, HL7, DICOM, SCP
- Support wireless transmission of ECG data via WiFi and mobile networks
- Support laser printer via USB port and network printer

# Specifications

Main Unit	
HR range	30 bpm ~ 300 bmp
Accuracy	± 1
A/D conversion	24 bits
Sampling rate	32000 samples/Sec
Common mode rejection ratio	≥ 140 dB (AC filter on) ≥ 120 dB (AC filter off)
Time constant	≥ 5 sec
Frequency response	0.01 Hz ~ 350 Hz (+0.4 dB-3.0 dB)
Sensitivity	Auto. 2.5 mm/mV, 5 mm/mV, 10 mm/mV, 20 mm/mV, 40 mm/mV, less than ± 5% error
Filter	AC filter: 50 Hz, 60 Hz, Off EMG filter: 25 Hz, 35 Hz, 45 Hz, Off ADS filter: 0.01 Hz, 0.05 Hz, 0.32 Hz, 0.67 Hz Low pass filter: 75 Hz, 100 Hz, 150 Hz, 300 Hz, Off
Paper speed	5 mm/s, 6,25 mm/s, 10mm/s, 12,5 mm/s, 25 mm/s and 50 mm/ms, less than ± 3% error
Input Impedance	≥100MΩ (10Hz)
Standard accessory	ECG cable, Precordial Suction Electrodes, Limp Clamp Electrodes, rechargeable battery, Power cord, 7" leather sheath, USB-Stick
Optional accessory	Transportation Bag
Languages	German, English, Polish, Spanish, Portuguese, French, Italian, Greek, Chinese, Russian
Dimensions	Size: (LWH) 197 mm x 112,4 mm x 26,1 mm Net Weight: 0,8 kg
Analysis algorithm	Glasgow



## Optional Accessory:



Im Erlengrund 16, 46149 Oberhausen - Germany  
 t: +49 (0) 208 377 890-0 info@medical-econet.com  
 f: +49 (0) 208 377 890-55 www.medical-econet.com  
 facebook.com/medicaleconetgermany  
 twitter.com/medicaleconet

Distributor

\*Subject to change without notice